



A business of MSC Industrial Supply Co.

## Safety Data Sheet

### Supply Co. - GLOSS RED, BD13400000

Document Nbr: 076398  
Class C Parts IDs BD1340,BD1340-1

S(R\*)  
SEYMOUR(R\*)

SAFETY DATA SHEET

PRINTING DATE: 02/16/2015

REVISED ON: 02/16/2015

-----1 IDENTIFICATION OF THE SUBSTANCE AND MANUFACTURER -----

TRADE NAME: GLOSS RED

PRODUCT CODE: BD13400000

PRODUCT CATEGORY:  
PC9A: PAINTS AND COATINGS.

MANUFACTURER/SUPPLIER:  
SEYMOUR OF SYCAMORE  
917 CROSBY AVENUE  
SYCAMORE, IL 60178

PHONE: 815-895-9101

WWW.SEYMOURPAINT.COM

EMERGENCY TELEPHONE NUMBER:  
CHEMTEL: 1-800-255-3924, OR 813-248-0585.

-----2 HAZARD(S) IDENTIFICATION -----

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE:

FLAM. AEROSOL 1:  
H222: EXTREMELY FLAMMABLE AEROSOL.

## PRESS. GAS:

H280: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

## CARC. 2:

H351: SUSPECTED OF CAUSING CANCER.

## REPR. 2:

H361: SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.

## STOT RE 2:

H373: MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

## SKIN IRRIT. 2:

H315: CAUSES SKIN IRRITATION.

## EYE IRRIT. 2A:

H319: CAUSES SERIOUS EYE IRRITATION.

## STOT SE 3:

H336: MAY CAUSE DROWSINESS OR DIZZINESS.

## GHS HAZARD PICTOGRAMS:

GHS02: FLAME

GHS04: GAS CYLINDER

GHS07: EXCLAMATION MARK

GHS08: HEALTH HAZARD

## SIGNAL WORD: DANGER

## HAZARD STATEMENTS:

EXTREMELY FLAMMABLE AEROSOL.

CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

CAUSES SKIN IRRITATION.

CAUSES SERIOUS EYE IRRITATION.

SUSPECTED OF CAUSING CANCER.

SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.

MAY CAUSE DROWSINESS OR DIZZINESS.

MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

## PRECAUTIONARY STATEMENTS:

IF MEDICAL ADVICE IS NEEDED, HAVE PRODUCT CONTAINER OR LABEL AT HAND.

KEEP OUT OF REACH OF CHILDREN.

READ LABEL BEFORE USE.

OBTAIN SPECIAL INSTRUCTIONS BEFORE USE.

KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT SURFACES. - NO SMOKING.

DO NOT SPRAY ON AN OPEN FLAME OR OTHER IGNITION SOURCE.

PRESSURIZED CONTAINER: DO NOT PIERCE OR BURN, EVEN AFTER USE.

WASH HANDS THOROUGHLY AFTER HANDLING.

USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.

WEAR PROTECTIVE GLOVES/PROTECTIVE CLOTHING/EYE PROTECTION/FACE PROTECTION.

DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD.

WEAR PROTECTIVE GLOVES.

DO NOT BREATHE DUST/FUME/GAS/MIST/VAPORS/SPRAY.

IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING.

IF IN EYES:

RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING.

CALL A POISON CENTER/DOCTOR IF YOU FEEL UNWELL.

IF SKIN IRRITATION OCCURS: GET MEDICAL ADVICE/ATTENTION.

IF ON SKIN: WASH WITH PLENTY OF WATER.

IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ATTENTION.

TAKE OFF CONTAMINATED CLOTHING AND WASH IT BEFORE REUSE.

STORE LOCKED UP.

PROTECT FROM SUNLIGHT. DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50 DEG. C/122 DEG. F.

STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED.

DISPOSE OF CONTENTS/CONTAINER IN ACCORDANCE WITH LOCAL/REGIONAL/NATIONAL/INTERNATIONAL REGULATIONS.

-----3 COMPOSITION/INFORMATION ON INGREDIENTS -----

CHEMICAL CHARACTERIZATION: MIXTURES

CHEMICAL DESCRIPTION:

THIS PRODUCT IS A MIXTURE OF THE SUBSTANCES LISTED BELOW WITH NONHAZARDOUS ADDITIONS.

DANGEROUS COMPONENTS:

67-64-1	ACETONE	35.28%
---------	---------	--------

74-98-6	PROPANE	15.75%
108-88-3	TOLUENE	11.07%
106-97-8	N-BUTANE	9.25%
108-65-6	PM ACETATE	4.55%
108-10-1	METHYL ISOBUTYL KETONE	1.87%
107-87-9	METHYL PROPYL KETONE	1.67%
2807-30-91	GLYCOL ETHER EP	1.45%

-----4 FIRST-AID MEASURES -----

AFTER INHALATION: SUPPLY FRESH AIR; CONSULT DOCTOR IN CASE OF COMPLAINTS.

AFTER SKIN CONTACT:

REMOVE CONTAMINATED CLOTHING. WASH EXPOSED AREA WITH SOAP AND WATER.

AFTER EYE CONTACT:

RINSE OPENED EYE FOR SEVERAL MINUTES UNDER RUNNING WATER. IF SYMPTOMS PERSIST, CONSULT A DOCTOR.

AFTER SWALLOWING:

RINSE OUT MOUTH AND THEN DRINK PLENTY OF WATER.  
RINSE MOUTH WITH WATER. DO NOT INDUCE VOMITING.

MOST IMPORTANT SYMPTOMS AND EFFECTS: DIZZINESS

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION NEEDED:

NO FURTHER RELEVANT INFORMATION AVAILABLE.

-----5 FIRE-FIGHTING MEASURES -----

EXTINGUISHING AGENTS:

CO<sub>2</sub>, EXTINGUISHING POWDER OR WATER SPRAY. FIGHT LARGER FIRES WITH WATER SPRAY.

SPECIAL HAZARDS: CAN FORM EXPLOSIVE GAS-AIR MIXTURES.

PROTECTIVE EQUIPMENT FOR FIREFIGHTERS:

A RESPIRATORY PROTECTIVE DEVICE MAY BE NECESSARY.

-----6 ACCIDENTAL RELEASE MEASURES -----

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

WEAR PROTECTIVE EQUIPMENT. KEEP UNPROTECTED PERSONS AWAY.

USE RESPIRATORY PROTECTIVE DEVICE AGAINST THE EFFECTS OF FUMES/DUST/AEROSOL.

METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:  
ENSURE ADEQUATE VENTILATION.  
DISPOSE CONTAMINATED MATERIAL AS WASTE ACCORDING TO SECTION 13.

-----7 HANDLING AND STORAGE -----

PRECAUTIONS FOR SAFE HANDLING: USE ONLY IN WELL VENTILATED AREAS.

STORAGE REQUIREMENTS:  
KEEP AWAY FROM SOURCES OF HEAT AND DIRECT SUNLIGHT. DO NOT WAREHOUSE IN  
SUBFREEZING CONDITIONS. STORE LOCKED UP.

-----8 EXPOSURE CONTROLS/PERSONAL PROTECTION -----

COMPONENTS WITH LIMIT VALUES THAT REQUIRE MONITORING AT THE WORKPLACE:

67-64-1 ACETONE:

PEL (USA):  
LONG-TERM VALUE: 2400 MG/M3, 1000 PPM

REL (USA):  
LONG-TERM VALUE: 590 MG/M3, 250 PPM

TLV (USA):  
SHORT-TERM VALUE: (1782) NIC-1187 MG/M3, (750) NIC-500 PPM  
LONG-TERM VALUE: (1188) NIC-594 MG/M3, (500) NIC-250 PPM  
BEI

74-98-6 PROPANE:

PEL (USA):  
LONG-TERM VALUE: 1800 MG/M3, 1000 PPM

REL (USA):  
LONG-TERM VALUE: 1800 MG/M3, 1000 PPM

TLV (USA): REFER TO APPENDIX F

108-88-3 TOLUENE:

PEL (USA):  
LONG-TERM VALUE: 200 PPM  
CEILING LIMIT VALUE: 300; 500\* PPM

\*10-MIN PEAK PER 8-HR SHIFT

REL (USA):  
SHORT-TERM VALUE: 560 MG/M3, 150 PPM  
LONG-TERM VALUE: 375 MG/M3, 100 PPM

TLV (USA):  
LONG-TERM VALUE: 75 MG/M3, 20 PPM  
BEI

106-97-8 N-BUTANE:

REL (USA):  
LONG-TERM VALUE: 1900 MG/M3, 800 PPM

TLV (USA):  
SHORT-TERM VALUE: 2370 MG/M3, 1000 PPM

108-65-6 PM ACETATE:

WEEL (USA):  
LONG-TERM VALUE: 50 PPM

108-10-1 METHYL ISOBUTYL KETONE:

PEL (USA):  
LONG-TERM VALUE: 410 MG/M3, 100 PPM

REL (USA):  
SHORT-TERM VALUE: 300 MG/M3, 75 PPM  
LONG-TERM VALUE: 205 MG/M3, 50 PPM

TLV (USA):  
SHORT-TERM VALUE: 307 MG/M3, 75 PPM  
LONG-TERM VALUE: 82 MG/M3, 20 PPM  
BEI

107-87-9 METHYL PROPYL KETONE:

PEL (USA):  
LONG-TERM VALUE: 700 MG/M3, 200 PPM

REL (USA):  
LONG-TERM VALUE: 530 MG/M3, 150 PPM

TLV (USA):  
SHORT-TERM VALUE: 529 MG/M3, 150 PPM

INGREDIENTS WITH BIOLOGICAL LIMIT VALUES:

67-64-1 ACETONE:  
BEI (USA): 50 MG/L  
MEDIUM: URINE  
TIME: END OF SHIFT  
PARAMETER: ACETONE (NONSPECIFIC)

108-88-3 TOLUENE:

BEI (USA):  
0.02 MG/L  
MEDIUM: BLOOD  
TIME: PRIOR TO LAST SHIFT OF WORKWEEK  
PARAMETER: TOLUENE

0.03 MG/L  
MEDIUM: URINE  
TIME: END OF SHIFT  
PARAMETER: TOLUENE

0.3 MG/G CREATININE  
MEDIUM: URINE  
TIME: END OF SHIFT  
PARAMETER: O-CRESOL WITH HYDROLYSIS (BACKGROUND)

108-10-1 METHYL ISOBUTYL KETONE:  
BEI (USA): 1 MG/L  
MEDIUM: URINE  
TIME: END OF SHIFT  
PARAMETER: MIBK

HYGIENIC PROTECTION:  
KEEP AWAY FROM FOODSTUFFS AND ANIMAL FEED. WASH HANDS AFTER USE.  
IMMEDIATELY REMOVE ALL SOILED AND CONTAMINATED CLOTHING.  
WASH HANDS AFTER USE.  
AVOID CONTACT WITH THE EYES AND SKIN.  
DO NOT EAT OR DRINK WHILE WORKING.

BREATHING EQUIPMENT:  
A RESPIRATOR IS GENERALLY NOT NECESSARY WHEN USING THIS PRODUCT OUTDOORS  
OR IN LARGE OPEN AREAS. IN CASES WHERE SHORT AND/OR LONG TERM OVEREXPOSURE  
EXISTS, A CHARCOAL FILTER RESPIRATOR SHOULD BE WORN. IF YOU SUSPECT  
OVEREXPOSURE CONDITIONS EXIST, PLEASE CONSULT AN AUTHORITY ON CHEMICAL  
HYGIENE.

HAND PROTECTION:  
PROTECTIVE GLOVES. THE GLOVE MATERIAL MUST BE IMPERMEABLE AND RESISTANT  
TO THE SUBSTANCE.

EYE PROTECTION: TIGHTLY SEALED GOGGLES

-----9 PHYSICAL AND CHEMICAL PROPERTIES -----

APPEARANCE: AEROSOL.

ODOR: AROMATIC

ODOR THRESHOLD: NOT DETERMINED.

PH-VALUE: NOT DETERMINED.

MELTING POINT/MELTING RANGE: UNDETERMINED.

BOILING POINT: -44 DEG. C (-47 DEG. F)

FLASH POINT: -19 DEG. C (-2 DEG. F)

FLAMMABILITY (SOLID, GAS): EXTREMELY FLAMMABLE.

DECOMPOSITION TEMPERATURE: NOT DETERMINED.

AUTO IGNITING: PRODUCT IS NOT SELF-IGNITING.

DANGER OF EXPLOSION:

IN USE, MAY FORM FLAMMABLE/EXPLOSIVE VAPOUR-AIR MIXTURE.

LOWER EXPLOSION LIMIT: 1.7 VOL %

UPPER EXPLOSION LIMIT: 10.9 VOL %

VAPOR PRESSURE: NOT DETERMINED.

RELATIVE DENSITY: BETWEEN 0.77 AND 0.85 (WATER EQUALS 1.00)

VAPOUR DENSITY: NOT DETERMINED.

EVAPORATION RATE: NOT APPLICABLE.

PARTITION COEFFICIENT N-OCTONAL/WATER: NOT DETERMINED.

SOLUBILITY: NOT DETERMINED.

VISCOSITY: NOT DETERMINED.

VOC CONTENT: 527.8 G/L / 4.40 LB/GL

VOC CONTENT (LESS EXEMPT SOLVENTS): 46.6%

MIR VALUE: 1.08

SOLIDS CONTENT: 18.1%

-----10 STABILITY AND REACTIVITY -----

REACTIVITY: STABLE AT NORMAL TEMPERATURES.

CONDITIONS TO AVOID:

DO NOT ALLOW CAN TO EXCEED 120 DEGREES FAHRENHEIT. DO NOT WAREHOUSE IN  
SUBFREEZING TEMPERATURES.

CHEMICAL STABILITY: NOT FULLY EVALUATED.

POSSIBILITY OF HAZARDOUS REACTIONS: NO DANGEROUS REACTIONS KNOWN.



AQUATIC TOXICITY: HAZARDOUS FOR WATER, DO NOT EMPTY INTO DRAINS.

PERSISTENCE AND DEGRADABILITY:

THE PRODUCT IS DEGRADABLE AFTER PROLONGED EXPOSURE TO NATURAL WEATHERING PROCESSES.

BIOACCUMULATIVE POTENTIAL: NO FURTHER RELEVANT INFORMATION AVAILABLE.

MOBILITY IN SOIL: NO FURTHER RELEVANT INFORMATION AVAILABLE.

OTHER ADVERSE EFFECTS: NO FURTHER RELEVANT INFORMATION AVAILABLE.

-----13 DISPOSAL CONSIDERATIONS -----

DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS. DO NOT PUNCTURE, INCINERATE, OR COMPACT. PARTIALLY EMPTY CANS MUST BE DISPOSED OF RESPONSIBLY. DO NOT HEAT OR CUT EMPTY CONTAINERS WITH ELECTRIC OR GAS TORCHES.

RECOMMENDATION: COMPLETELY EMPTY CANS SHOULD BE RECYCLED.

-----14 TRANSPORT INFORMATION -----

UN-NUMBER: UN1950

DOT:

N/A

UN1950

DOT: CONSUMER COMMODITY AEROSOLS, FLAMMABLE

ADR: 1950 AEROSOLS

TRANSPORT HAZARD CLASS(ES):

CLASS: 2.1

MARINE POLLUTANT: NO

SPECIAL PRECAUTIONS FOR USER:

WARNING: GASES

EMS NUMBER: F-D, S-U

PACKAGING GROUP:

UN "MODEL REGULATION": UN1950, AEROSOLS, 2.1

-----15 REGULATORY INFORMATION -----

